

## 16W Med EL/A R30 Dim ALTO 1CT

Product family description Similar look and light output as a 65 Watt incandescent BR30 reflector flood. Diffused, Soft White Light - Wide flood provides smooth, even lighting without hot spots.

Suitable for use in wet locations. Amalgram Technology - Provides stable light over a broad range of temperatures. Super Long Life - Lasts 5 years, based on 3-4 hours average daily usage, 7 days per week (up to 7 times longer than standard incandescent lamps).

Energy Savings - Saves up to 75% in electricity costs compared to incandescent lamps.

ENERGY STAR Qualified.

## Applications

• Ideal for recessed and track lighting fixtures, indoors and outdoors.

## Notes

- The use of Amalgam Technology results in relatively stable light output across a broad range of ambient temperatures and operating positions. (216)
- All Marathon<sup>™</sup> lamps are suitable for indoor or outdoor use down to -10°F. Outdoor use requires a weatherprotected fixture. All these products comply with part 18 of the FCC rules. These products may cause interference with AM radios, cordless telephones, and remote control devices. Interference may be caused after a brief 90second lamp warm-up period. If interference continues, relocate the lamp away from the device or plug into a different outlet. (217)
- All lamps are electronically ballasted and designed for 120 volt operation. Lamps operated in extreme environments will have reduced life (ie. recessed or enclosed lighting fixtures with elevated line voltage). Caution: except for lamps marked dimmable, do not use with dimmers. Before using these lamps with electronic timing or photocell devices, check to determine whether the device is compatible with compact fluorescent lamps. Use with incompatible devices will result in premature lamp failure. These products are UL listed. (218)
- Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. (230)
- Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions. (231)

30 Dim ALTO 1CT IMM REFLECTOR
IMM DEELECTOD
ININI REFLECTOR
ling Carton
71
7



Product data	
Successor Product number	
Base	Medium [Single Contact Medium Screw]
Bulb	EL/A R30
Packing Type	1CT [1 Lamp in a Folding Carton]
Packing Configuration	6
Feature	Dimmable ALTO®
Rated Avg. Life [3 hr Start]	8000 hr
Ordering Code	EL/A R30 16W DIMM REFLECTOR
Pack UPC	046677137076
Case Bar Code	50046677137071
Energy Saving	Energy Saving
Watts	16W
Color Rendering Index	82 Ra8
Color Temperature	2700 K
Initial Lumens	630 Lm
Max Overall Length (MOL) - C	5.39 in
Product Number	137075



CI ReflD Medium EL/A R30

Energy Saving Product

Energy Saving Energy Saving



Base Medium

