



OTTICA EXIT

Cylindrical Edge-Lit Exit (Aluminum)



Project Name: _____ Model Number: _____
 Prepared By: _____ Date: _____

FEATURES & BENEFITS

- Extruded aluminum cylindrical design
- Edge-Lit LED technology
- AC Only, Self-Powered or Universal DC
- White, clear or mirrored face
- Surface wall, ceiling or end mounting (rectangular lens only)
- CSA 22.2 No.141-15 Performance Certified


BATTERY TECHNOLOGY

Designed with a maintenance free, nickel-cadmium battery providing a minimum emergency duration of 30 minutes. Recharge time of the battery is 24 hours.

BEGHELLI AUTO-TEST (AT)

The Beghelli auto-test system automatically performs one 5 minute discharge test monthly and every 6 months it performs two 30 minute discharge tests, 24 hours apart. This tests both full battery capacity and recharge capability, as required by the fire code.

DIMENSIONS



EXTERNAL SPECIFICATIONS

The OTTICA series cylindrical housing is constructed as a single piece from extruded aluminum. The canopy is made from sturdy die-cast aluminum and the end caps from machined aluminum. The high clarity acrylic faceplate is available in both single face or double face versions, with a clear, white or mirrored background (please specify). White, baked powder coat finish is standard on all versions. Available in custom colours and finishes (please specify). External LED monitor light and test switch are standard on self-powered versions.

INTERNAL SPECIFICATIONS

AC ONLY, AC/DC and SELF-POWERED: comes standard configured with high-output LED technology and 120/347VAC input. Nickel-cadmium batteries provide a minimum 30 minutes of emergency duration. Solid state charger & transfer. OTTICA exits configured for AC/DC operation feature a universal 2 wire DC output; 6VDC - 24VDC backup voltages are standard. If an AC generator is used to back up the signs, a surge suppression device is recommended to protect the entire emergency circuit.

ORDERING GUIDE

OT-E - - - - -

SERIES	OPERATION	LIGHT SOURCE	LETTER COLOUR	FACE#	MOUNTING	CHEVRONS	OPTIONS
OT-E (Exit)	Blank (AC only) SP (Self-powered)	L (LED)	ROC (Red on clear - single face only) ROW (Red on white) ROM (Red on mirror)	1 (Single) 2 (Double)	WC (Wall & Ceiling) E (End)	U (Field adjustable)	OV (Oval shaped face) CC (Custom colour - specify) AT (Auto test, SP only) BA (Brushed aluminum finish) PA (Polished aluminum finish) SW (Special wording - specify) PK12 (12" pendant kit) UDC (Universal 6 - 24VDC) 90SP (90 min. emergency) 120SP (120 min. emergency) IF (Inverted face)