



					IS=Instant Start ballast			PS=Program Start ballast		PRS=Program Rapid Start ballast				
Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Rated life IS (3 hrs)	Rated life IS (12 hrs)	Rated life PS/PRS (3 hrs)	Rated life PS/PRS (12 hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length in. (mm)	Efficacy (lm/W)	Case qty
Appliance														
10507	F16T8/CW/APL/26/PH/G13/STD	16	G13*	4 100	62	6 000	7 500	N/A	N/A	1 275	1 199	26 (660)	80	48
10508	F17T8/CW/APL/28/PH/G13/STD	17	G13	4 100	62	6 000	7 500	N/A	N/A	1 350	1 269	28 (711)	79	48
10506	F18T8/CW/APL/24/PH/G13/STD	18	G13	4 100	62	6 000	7 500	N/A	N/A	1 225	1 152	24 (610)	68	48
10509	F18T8/CW/APL/30/PH/G13/STD	18	G13	4 100	62	6 000	7 500	N/A	N/A	1 400	1 316	30 (762)	78	100
Metric														
10496	F32T8/35K/8/RS/G13/METRIC/STD	32	G13	3 500	85	24 000	30 000	30 000	36 000	2 800	2 650	46 (1 168)	88	25
10497	F32T8/41K/8/RS/G13/METRIC/STD	32	G13	4 100	85	24 000	30 000	30 000	36 000	2 800	2 650	46 (1 168)	88	25
10498	F32T8/FS/RS/G13/METRIC/STD	32	G13	5 700	92	15 000	24 000	20 000	28 000	1 850	1 750	46 (1 168)	58	25
Cold Start														
59244	F32T8/41K/8/RS/G13/COLDSTART/STD	32	G13	4 100	85	24 000	30 000	30 000	36 000	2 600	2 450	48 (1 220)	81	25
59243	F54T5/41K/8/HO/PS/G5/COLDSTART/STD	54	G5**	4 100	85	24 000	30 000	30 000	36 000	4 650	4 400	48 (1 220)	86	25
Coloured														
51171	F32T8/GLD/RS/G13/STD	32	G13	2 300	N/A	10 000	13 000	13 000	15 000	N/A	N/A	48 (1 220)	N/A	25
51177	F32T8/BL/RS/G13/STD	32	G13	N/A	N/A	8 000	10 000	10 000	12 000	N/A	N/A	48 (1 220)	N/A	25
51173	F32T8/BLB/RS/G13/STD	32	G13	N/A	N/A	8 000	10 000	10 000	12 000	N/A	N/A	48 (1 220)	N/A	25
Plant Light														
51176	F32T8/PLA/RS/G13/STD	32	G13	N/A	N/A	15 000	24 000	20 000	28 000	1 450	1 350	48 (1 220)	45	25
RGB (Red / Green / Blue)														
51175	F32T8/RS/G13/STD RGB	32	G13	N/A	82	15 000	24 000	20 000	28 000	1 650	1 550	48 (1 220)	52	25

* G13 = Med Bipin

** G5 = Min Bipin

¹ One year warranty on lamps with less than 18 000 hours average life

² Two year warranty on lamps with more than 18 000 hours average life



Specialty