





INSULATED CEILING "IC" TYPE HOUSINGS


MODEL	OD CUT	DIAMETER	LIGHT SOURCE	TRANSFORMER CONVERTER
ISMR3000M20	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	MR16 - 20W	EC20M 20 VA. 120 V. / 12V.
ISMR3000E20	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	MR16 - 20W	ELEC.CONV. 120 V. / 12V.
ISMR3000E202	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	MR16 - 20W	ELEC.CONV. 277 V. / 12V.
ISMR4000M20	3 5/16" 84 mm	Ø 3" (76 mm)	MR16 - 20W	EC20M 20 VA. 120 V. / 12V.
ISCA2000	4 5/16" 109 mm	Ø 4" (102 mm)	PAR 20 50W	BALLAST 120V (H.P.F.) BALLAST 120V (H.P.F.) BALLAST 120V (H.P.F.)
ISCA2000D	4 5/16" 109 mm	Ø 4" (102 mm)	PAR 20 50W	
ISCA2550	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	PAR 20 50W	
ISCA3600	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	PAR 20 50W	
ISCA2675	4 5/8" 118 mm	Ø 4 5/16" (110 mm)	PAR 30 75W	
ISF2000	4 5/16" 109 mm	Ø 4" (102 mm)	PL13W QUAD	
ISF2575R	4 5/8" 118 mm	Ø 4 5/16" (110 mm)	PL13W QUAD	
ISF2675R	4 5/8" 118 mm	Ø 4 5/16" (110 mm)	PL13W QUAD	




ISMR2000E35	4 5/16" 109 mm	Ø 4" (102 mm)	MR16 - 35W	ELEC.CONV. 120 V. / 12V.
ISMR2000E352	4 5/16" 109 mm	Ø 4" (102 mm)	MR16 - 35W	ELEC.CONV. 277 V. / 12V.
ISMR3000E35	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	MR16 - 35W	ELEC.CONV. 120 V. / 12V.
ISMR3000E352	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	MR16 - 35W	ELEC.CONV. 277 V. / 12V.
ISCA2575	4 5/8" 118 mm	Ø 4 5/16" (110 mm)	PAR 30 75W	



ISMR7000E35	4 5/16" 109 mm	Ø 4 1/16" (103 mm)	MR16 - 35W	ELEC.CONV. 120 V. / 12 V.
ISMR7000E352	4 5/16" 109 mm	Ø 4 1/16" (103 mm)	MR16 - 35W	ELEC.CONV. 277 V. / 12 V.
ISMR7000M35	4 5/16" 109 mm	Ø 4 1/16" (103 mm)	MR16 - 35W	EC50M 50 VA. 120 V. / 12 V.
ISMR7000M352	4 5/16" 109 mm	Ø 4 1/16" (103 mm)	MR16 - 35W	EC50M 50 VA. 277 V. / 12 V.
ISMR7000M353	4 5/16" 109 mm	Ø 4 1/16" (103 mm)	MR16 - 35W	EC50M 50 VA. 347 V. / 12 V.



ISMR2000M	4 5/16" 109 mm	Ø 4" (102 mm)	MR16 - 50W	EC50M 50 VA. 120 V. / 12 V.
ISMR2000M2	4 5/16" 109 mm	Ø 4" (102 mm)	MR16 - 50W	EC50M 50 VA. 277 V. / 12 V.
ISMR2000M3	4 5/16" 109 mm	Ø 4" (102 mm)	MR16 - 50W	EC50M 50 VA. 347 V. / 12 V.
ISMR2000T	4 5/16" 109 mm	Ø 4" (102 mm)	GU/GZ 10 - 50W	
ISMR3000M	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	MR16 - 50W	EC50M 50 VA. 120 V. / 12 V.
ISMR3000M2	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	MR16 - 50W	EC50M 50 VA. 277 V. / 12 V.
ISMR3000M3	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	MR16 - 50W	EC50M 50 VA. 347 V. / 12 V.
ISMR3000T	3 3/4" 95 mm	Ø 3 1/2" (89 mm)	GU/GZ 10 - 50W	



EQUIPPED WITH THERMAL PROTECTION AND APPROVED FOR DAMP LOCATION.
AIR TIGHT PRODUCT.
FIRE RATED.