


## TECHNICAL INFORMATION BULLETIN

## Pulse Start System

Pulsetek<sup>TM</sup>

## Ordering Information

Order code: 58027  
 Description: MP320W/C/BU/ED28/UVS/PS/737 STD  
 UPC: 69549580275  
 Case quantity: 12  
 ANSI code: M154/O




## Performance Data

Wattage (W):	320
Initial lumens (lm):	29 000
Mean lumens (lm):	23 200
Lumens per watt (lm/W):	91
Lamp voltage (V):	135
Colour temperature (K):	3 700
Chromaticity (x,y):	0.395, 0.390
CRI:	70
Average life (hrs):	20 000
Lamp lumen depreciation:	0.86% @ 8 000 hrs
Warm up time to 90% (min):	2-3
Hot restart time to 90% (min):	5-8
Burn Position:	Base Up $\pm 15^\circ$
Dimming:	50% rated power
Max base temperature:	230
Max lamp temperature:	450
Socket pulse rating (kV):	4



## Spectral Distribution



## Physical data / Requirements

Shape:	ED28
Base:	EX39
Finish:	Coated
Luminaire rating:	Open Rated
Diameter (mm/in.):	89.0 (3 1/2)
MOL (mm/in.):	211.0 (8 5/16)
LCL (mm/in.):	127.0 (5)
Effective arc length (mm):	N/A
Mercury Content (mg):	50

## Warning

**“R” WARNING:** this lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if the outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Complies with USA Federal Standard 21 CFR 1040.30 and Canada Standard SOR/80-381.