


# T3 & T4 SPIRALS



## Features

- Unique spiral design shortens the length of the lamp
- Minimal light trapping creating more light output
- Light distribution very close to incandescent
- Operating temperatures:  
-18°C/0°F to 50°C/123°F
-  Visit our website for a complete listing of all STANDARD ENERGY STAR qualified products

26 Watts



MOL = 5 7/8 in. (138 mm)  
Dia. = 2 5/8 in. (59 mm)

32 Watts



MOL = 6 3/8 in. (155 mm)  
Dia. = 2 5/8 in. (67 mm)

40 Watts



MOL = 7 9/16 in. (185 mm)  
Dia. = 2 5/8 in. (67 mm)

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)
------------	-------------	-----------	------	------------------	-----	--------------------	---------------------	----------	-----------------------------

### T3 Spirals

58406	CF26/30K/SPIRAL/E26/STD	26	E26	3 000	82	10 000	1 850	48	100
58407	CF26/35K/SPIRAL/E26/STD	26	E26	3 500	82	10 000	1 850	48	100
58408	CF26/41K/SPIRAL/E26/STD	26	E26	4 100	82	10 000	1 850	48	100
14161	CF26/50K/SPIRAL/E26/STD	26	E26	5 000	82	10 000	1 850	48	100
58409	CF26/65K/SPIRAL/E26/STD	26	E26	6 500	82	10 000	1 850	48	100
58442	CF27/27K/SPIRAL/E26/STD	27	E26	2 700	82	10 000	1 850	48	100

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)
------------	-------------	-----------	------	------------------	-----	--------------------	---------------------	----------	-----------------------------

### T4 Spirals

60932	CF32/27K/SPIRAL/E26/STD	32	E26	2 700	82	10 000	2 000	48	120
56274	CF32/30K/SPIRAL/E26/STD	32	E26	3 000	82	10 000	2 100	48	120
58410	CF32/35K/SPIRAL/E26/STD	32	E26	3 500	82	10 000	2 100	48	120
58411	CF32/41K/SPIRAL/E26/STD	32	E26	4 100	82	10 000	2 100	48	120
60936	CF32/50K/SPIRAL/E26/STD	32	E26	5 000	82	10 000	2 000	48	120
58412	CF32/65K/SPIRAL/E26/STD	32	E26	6 500	82	10 000	2 100	48	120
60939	CF40/30K/SPIRAL/E26/STD	40	E26	3 000	82	10 000	2 600	48	150
60940	CF40/35K/SPIRAL/E26/STD	40	E26	3 500	82	10 000	2 600	48	150
60941	CF40/41K/SPIRAL/E26/STD	40	E26	4 100	82	10 000	2 600	48	150
60942	CF40/50K/SPIRAL/E26/STD	40	E26	5 000	82	10 000	2 600	48	150
60943	CF40/65K/SPIRAL/E26/STD	40	E26	6 500	82	10 000	2 600	48	150