

T2 spirals have a super mini size that fits most fixtures. The ballast's new design allows for more versatile applications and use of amalgam enables the lamps to work at lower temperatures, starting at -23 °C/-10 °F to 55 °C/131 °F.



Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)
5 watts MOL: 3 1/8 in. (79 mm) Dia.: 1 7/32 in. (39 mm)									
58391	CF5/27K/SPIRAL/E12/STD	5	E12	2 700	82	8 000	250	48	25
MOL: 3 3/32 in. (88 mm) Dia.: 1 7/32 in. (39 mm)									
60930	CF5/27K/SPIRAL/E26/STD	5	E26	2 700	82	10 000	270	48	25
9 watts MOL: 3 3/32 in. (90 mm) Dia.: 1 5/32 in. (45 mm)									
62827	CF9/T2/27K/SPIRAL/E26/STD	9	E26	2 700	82	12 000	550	96	40
13 watts MOL: 4 1/32 in. (104 mm) Dia.: 1 11/32 in. (50 mm)									
62828	CF13/T2/27K/SPIRAL/E26/STD	13	E26	2 700	82	12 000	900	48	60
62829	CF13/T2/35K/SPIRAL/E26/STD	13	E26	3 500	82	12 000	900	48	60
62830	CF13/T2/41K/SPIRAL/E26/STD	13	E26	4 100	82	12 000	900	48	60
62831	CF13/T2/50K/SPIRAL/E26/STD	13	E26	5 000	82	12 000	900	48	60
18 watts MOL: 4 11/32 in. (110 mm) Dia.: 2 1/32 in. (55 mm)									
62832	CF18/T2/27K/SPIRAL/E26/STD	18	E26	2 700	82	12 000	1 250	48	75
62833	CF18/T2/30K/SPIRAL/E26/STD	18	E26	3 000	82	12 000	1 250	48	75
62834	CF18/T2/35K/SPIRAL/E26/STD	18	E26	3 500	82	12 000	1 250	48	75
62835	CF18/T2/41K/SPIRAL/E26/STD	18	E26	4 100	82	12 000	1 250	48	75
62836	CF18/T2/50K/SPIRAL/E26/STD	18	E26	5 000	82	12 000	1 250	48	75
23 watts MOL: 4 15/32 in. (115 mm) Dia.: 2 3/8 in. (60 mm)									
62837	CF23/T2/27K/SPIRAL/E26/STD	23	E26	2 700	82	12 000	1 600	48	100
62838	CF23/T2/30K/SPIRAL/E26/STD	23	E26	3 000	82	12 000	1 600	48	100
62839	CF23/T2/35K/SPIRAL/E26/STD	23	E26	3 500	82	12 000	1 600	48	100
62840	CF23/T2/41K/SPIRAL/E26/STD	23	E26	4 100	82	12 000	1 600	48	100
62841	CF23/T2/50K/SPIRAL/E26/STD	23	E26	5 000	82	12 000	1 600	48	100
62842	CF23/T2/65K/SPIRAL/E26/STD	23	E26	6 500	82	12 000	1 600	48	100
26 watts MOL: 5 1/16 in. (129 mm) Dia.: 2 3/16 in. (54 mm)									
63388	CF26/T2/27K/SPIRAL/E26/STD	26	E26	2 700	82	10 000	1 750	48	100
63389	CF26/T2/30K/SPIRAL/E26/STD	26	E26	3 000	82	10 000	1 750	48	100
63390	CF26/T2/35K/SPIRAL/E26/STD	26	E26	3 500	82	10 000	1 750	48	100
63391	CF26/T2/41K/SPIRAL/E26/STD	26	E26	4 100	82	10 000	1 750	48	100
63392	CF26/T2/50K/SPIRAL/E26/STD	26	E26	5 000	82	10 000	1 750	48	100
58409	CF26/65K/SPIRAL/E26/STD	26	E26	6 500	82	10 000	1 850	50	100



Visit our website for a complete listing of all STANDARD ENERGY STAR qualified products.

T2 Spirals