

G9 BASED JD LAMPS are commonly refered to as G9 lamps.

dissiping heat. All STANDARD G9 based JD lamps are safe to use in open supported through glass pinch technology which minimizes deformation as well.









1

Order code	Description	Watts	Base	Volts	Colour/ Finish	Average life	Initial	Case
code		(W)		(V)	Finish	life (hrs)	lumens (lm)	qty
JD (G9) - Glass Base MOL: 1 <sup>21</sup> / <sub>12</sub> in. (42 mm) Dia: <sup>14</sup> / <sub>12</sub> in. (12 mm)								
58260	H25JD/42mm/CL/2M/G9/130V/STD	25	G9	130	Clear	2000	255	100
58257	H35JD/42mm/F/2M/G9/130V/STD	35	G9	130	Frost	2000	380	100
57259	H40JD/42MM/CL/2M/G9/130V/STD	40	G9	130	Clear	2000	480	100
57256	H40JD/42MM/F/2M/G9/130V/STD	40	G9	130	Frost	2000	480	100
57255	H50JD/42MM/CL/2M/G9/130V/STD	50	G9	130	Clear	2000	600	100
57261	H50JD/42MM/F/2M/G9/130V/STD	50	G9	130	Frost	2000	600	100
57258	H60JD/42MM/CL/2M/G9/130V/STD	60	G9	130	Clear	2000	800	100
57260	H60JD/42MM/F/2M/G9/130V/STD	60	G9	130	Frost	2000	800	100
58258	H75JD/42mm/CL/2M/G9/130V/STD	75	G9	130	Clear	2000	1050	100
JD (G9) - Ceramic Base MOL: 2 <sup>7</sup> / <sub>22</sub> in. (56 mm) Dia: <sup>11</sup> / <sub>12</sub> in. (12 mm)								
55057	H25JD/56MM/CL/2M/G9/120V/STD	25	G9	120	Clear	2000	255	100
55058	H40JD/56MM/CL/2M/G9/120V/STD	40	G9	120	Clear	2000	480	100
57253	H40JD/56MM/F/2M/G9/120V/STD	40	G9	120	Frost	2000	480	100
11247	H50JD/56MM/CL/2M/G9/120V/STD	50	G9	120	Clear	2000	600	100
15646	H50JD/56MM/F/2M/G9/120V/STD	50	G9	120	Frost	2000	600	100
55059	H60JD/56MM/CL/2M/G9/120V/STD	60	G9	120	Clear	2000	800	100
57257	H60JD/56MM/F/2M/G9/120V/STD	60	G9	120	Frost	2000	800	100
55060	H75JD/56MM/CL/2M/G9/120V/STD	75	G9	120	Clear	2000	1050	100



## JD Lamps